

Gregg - Dairy and Egg Crate



- Compatible with rigid dairy and egg crates currently used across the supply chain
- Collapsible design for freight optimization
- RFID smart technology enabled
- Optimal protection from pack house to Point of Sale (POS)
- Ergonomic design with IFCO Lift Lock
- Purpose built for egg and dairy applications



A sturdy, collapsible, food-safe reusable packaging container (RPC) for egg and dairy products. This RPC provides the durability of a rigid wall crate significantly reducing product damage during transport and storage then collapses after use for efficient backhaul shipping.

Your benefits

Optimal protection for fragile egg and dairy products

- Interlocking design for secure pallet-building
- Provides superior load weight support, minimizing compression-related damage
- Moisture-proof and does not weaken when exposed to humid environments

Ideal environment

- Optimum ventilation keeps products fresher for longer
- Damage reduction of up to 50% on fragile egg products
- Helps maintain proper temperatures along the cold chain

Better for your team and your supply chain

- RFID technology built-in to assist with supply chain transparency
- Dramatic reduction in broken eggs and crushed pallets means less clean up and restacking
- Standardized footprint assists with automation
- Eliminates the need to breakdown boxes and bale them

Efficient handling

- Fast manual or automated unfolding
- Easy stacking with minimum effort
- Compatible with rigid dairy and egg crates currently in use across the supply chain
- Folds for efficient use of space during backhaul shipping

Standardized for supply chain efficiency

- 3:1 transportation advantage over standard rigid wall crates
- Compatible with all standard pallets
- Purpose built for egg and dairy products
- Pooled and serviced through IFCO's network of service centers

Sustainable solution

- Reusable over many years, eliminating waste
- After useful life, material is fully recycled into new RPCs
- The Circular Economy at its best!
- Replaces single-use packaging with durable solution

Dimensions and specifications

Type		3335
Dimensions*	External dimensions (LxW)	330 x 330 mm / 13.0 x 13.0 in
	Total height	362 mm / 14.2 in
	Stacking height	353 mm / 13.9 in
	Usable internal height	353 mm / 13.9 in
	Folded height	117 mm / 4.6 in
	Folded stacking height	111 mm / 4.4 in
Logistics	Weight*	2.23 kg / 4.91 lb
	Maximum load	14.5 kg / 32 lb
	Number of RPCs per pallet (unfolded)	54 (40" x 48" pallet) / 72 (40" x 52" pallet)
	Number of layers on pallet (unfolded)	6
	Number of RPCs per pallet (folded)	198 (40" x 48" pallet) / 264 (40" x 52" pallet)
Material	Material	High Density Polyethylene
	Color	Black

* Dimensional and weight tolerance is +/-1,5%

Additional information

Temperature range Usable from 0°F to +150°F (-18°C to +66°C)

Properties Guaranteed long-life color intensity, UV radiation resistant, food safe

Notes on use

Unfolding



- 1 Pull up first two walls by gripping a handle with each hand
- 2 Pull green Lift Lock latch walls up with the handle until they lock into place
- 3 Check each corner that locking tabs are engaged

Folding



- 4 Unlock latch side walls by lifting the green Lift Locks and fold them down
- 5 Fold remaining sides down onto the base

Stacking



IFCO SYSTEMS US, LLC

For more information, visit [IFCO.com](https://www.ifco.com).

All information without guarantee and subject to change without notice.

© IFCO-DS1041-US-EN | 06/2023 | All Rights Reserved

